

LOKRITE Safety Backup Wrench



MAGNETIC Backup Nut for Hands Free Safety

- ✘ Zero Pinch Points
- ✘ Quick Release
- ✘ Fits in Tight Spaces
- ✘ Non-Sparking Area Use
- ✘ Promote Safe Bolting
- ✘ Reduces Hand Injuries

Magnetic Self Holding

The LOKRITE Backup Nut contains magnets embedded in one side that HOLD to any steel surface making it a true "Hands Free" device and PINCH POINT FREE.

Clever Quick-Release-Bolt allows easy removal while under TENSION with a simple half turn. No hammering them off your flange = less paint damage.

LOKRITE are perfect for Non-Striking & Non-Sparking torque applications, & difficult breakout applications.



Lokrite Standard AF Sizes:

AF NUT SIZE	For Stud Size
1-1/4"	3/4" Stud
1-7/16"	7/8" Stud
1-5/8"	1" Stud
1-13/16"	1 1/8" Stud
2"	1 1/4" Stud
2-3/16"	1 3/8" Stud
2-3/8"	1 1/2" Stud
2-9/16"	1 5/8" Stud
2-3/4"	1 3/4" Stud
2-15/16"	1 7/8" Stud
3-1/8"	2" Stud
3-1/2"	2 1/4" Stud
3-7/8"	2 1/2" Stud
4-1/4"	2 3/4" Stud
4-5/8"	3" Stud
5"	3 1/4" Stud
5-3/8"	3 1/2" Stud
5-3/4"	3 3/4" Stud
6-1/8"	4" Stud

Open-Ended LOKRITE Backup Nut

Fitting in tight spaces - a tight radius nose & low height clearance deals with restrictions.

Space issues are inherent safety concerns & the Open-Ended LOKRITE Backup Nut address & overcome these difficult applications.



LOKRITE Safety Backup Wrench with Magnetic Hold - truly Hands Free

Also in Standard Metric Sizes

Can be Custom Made to your Flange Stud Centres