

LOKRITE Safety Backup Wrench



MAGNETIC Backup Nut for Hands Free Safety

- ✘ Zero Pinch Points
- ✘ Quick Release
- ✘ Fits in Tight Spaces
- ✘ Non-Sparking Area Use
- ✘ Promote Safe Bolting
- ✘ Reduces Hand Injuries

Magnetic Self Holding

The LOKRITE Backup Nut contains magnets embedded in one side that HOLD to any steel surface making it a true "Hands Free" device and PINCH POINT FREE.

Clever Quick-Release-Bolt allows easy removal while under TENSION with a simple half turn. No hammering them off your flange = less paint damage.

LOKRITE are perfect for Non-Striking & Non-Sparking torque applications, & difficult breakout applications.



Lokrite Standard AF Sizes:

| AF NUT SIZE | For Stud Size |
|-------------|---------------|
| 1-1/4" | 3/4" Stud |
| 1-7/16" | 7/8" Stud |
| 1-5/8" | 1" Stud |
| 1-13/16" | 1 1/8" Stud |
| 2" | 1 1/4" Stud |
| 2-3/16" | 1 3/8" Stud |
| 2-3/8" | 1 1/2" Stud |
| 2-9/16" | 1 5/8" Stud |
| 2-3/4" | 1 3/4" Stud |
| 2-15/16" | 1 7/8" Stud |
| 3-1/8" | 2" Stud |
| 3-1/2" | 2 1/4" Stud |
| 3-7/8" | 2 1/2" Stud |
| 4-1/4" | 2 3/4" Stud |
| 4-5/8" | 3" Stud |
| 5" | 3 1/4" Stud |
| 5-3/8" | 3 1/2" Stud |
| 5-3/4" | 3 3/4" Stud |
| 6-1/8" | 4" Stud |

Open-Ended LOKRITE Backup Nut

Fitting in tight spaces - a tight radius nose & low height clearance deals with restrictions.

Space issues are inherent safety concerns & the Open-Ended LOKRITE Backup Nut address & overcome these difficult applications.



LOKRITE Safety Backup Wrench with Magnetic Hold - truly Hands Free

Also in Standard Metric Sizes

Can be Custom Made to your Flange Stud Centres