



Pneumatic Torque Wrench  
 Reversible non-Impacting  
*A Controlled Bolting Solution*

**3/4", 1" & 1 1/2" Square Drives** offer Smooth Continuous Rotation from 200 ft lbs to 11,500 ft lbs

Most advanced **Planetary Gear** reduction Gearbox driven by a precision air motor.

**Precision Spline** gives 360° reaction arm placement & nose extension control.

**Automatic 2 Speed** gearbox Models for high-speed rundown and single sequence precision tightening.

**Reaction Arm** Range adaptable to every situation.

**Simple Pistol Grip** Trigger & Reverse Switch operation

**Low Noise, High Power-to-Weight** ratio reducing operator strain. 88x less vibration than Rattle Guns with Zero hammering!

**Unmatched Power & Reliability** capable of accuracy of +/-5%, & repeatability of +/-2%.



**Complete with:**  
 Cradle + Hose  
 Regulator + Lubricator

Range covers **Pneumatic, Electronic, Electric, and Battery powered** Tools offering a complete solution





# Pneumatic Torque Nutrunner

Fast - Non Impacting - Accurate - Ultra Low Vibration - Simple to Use - Quiet



All RAD Air Tools come complete with:

- \* Standard Reaction Arm
- \* Regulator & Lubricator
- \* 3 metre Hose
- \* Tool Cradle with handle
- \* Heavy Duty Site Case.

Part Number	Model	Sq Drive	Torque Ft Lbs	Torque Nm	RPM	Weight
12316	350SL	3/4"	50 -350	70 - 475	65	2.7 kg
12814	7GX	3/4"	100 -700	130 - 950	30	3.6 kg
12818	10GX	3/4"	200 -1000	270 - 1,350	20	3.6 kg
17328	15DX	1"	300 -1,500	400 - 2,000	15	5.6 kg
12377	25GX	1"	500 -2,500	700 - 3,400	8	6.1 kg
12356	34GX	1"	1000 -3,400	1,400 - 4,600	12	9.0 kg
12357	50	1-1/2"	1,500 -5,000	2,000 - 6,800	7	12.7 kg
15328	60DX	1-1/2"	2,000 -6,000	2,700 - 8,130	6.6	12.7 kg
18558	80DX	1-1/2"	2500 - 8,000	3,400 - 10,800	4.2	13.6 kg
12383	85GX	1-1/2"	3000 -8,500	4,070 - 11,520	4.5	17.4 kg

**RAD Air Nut Runners -Perfect solution for accurate, repeatable torque.**

RAD Pneumatic Torque Tools use standard workshop 100PSI air at 30 cfm. Simply adjust the air regulator to set Torque Value - The tool will stall when correct torque is reached.





# Pneumatic Wrench NX Tool Kits



RAD NX Kits come with 3 Reaction Arms + Nose Extension covering Multiple Applications of high torque bolting




## NX Tool Kit Models

Part Number	Tool Model	Torque		Speed RPM	Nose Extension
		Ft.lbs	NM		
15517	7GX-NX	100-700	135-950	30	12"
13691	10GX-NX	200-1000	270-1350	20	12"
15518	1400NG-NX	300-1400	400-1900	15	12"
15519	1400NG-2-NX	500-1400	700-1900	69	12"
15520	1800NG-NX	500-1800	700-2450	10	12"
15521	1800NG-2-NX	700-1800	950-2450	53	12"
15522	25GX-NX	500-2500	700-3400	8	18"



**Complete with :**  
Cradle + Hose  
+ Regulator + Lubricator

**Comes in tough** dustproof / waterproof case

**Accuracy** - +/- 5%

Reduced Noise Levels - 80 db.

**Non Impacting:** Zero Hammering or Vibration

**High RPM :** Reduce Bolting time

**Controlled Torque :** Smooth Continuous Flow from 100 to 2500 ft lbs



**1/2 your time on common maintenance tasks!**

Packaging your RAD Tool of choice with a Nose Extension & 3 Reaction Arms covers every bolting applications